

**BASE BRAKES**

**NOTE:** Rotor runout specifications are not to be used for diagnosing brake concerns. The values in the table are post turn measurements taken by an on-vehicle brake lathe.

**SPECIFICATIONS**

DESCRIPTION	SPECIFICATION
Front Disc Brake Rotor Type	Ventilated
Rear Disc Brake Rotor Type	Ventilated
Rear Ventilated Disc Brake Rotor Max. Runout	0.020 mm (0.0008 in)
Front Ventilated Disc Brake Rotor Max. Runout	0.020 mm (0.0008 in)
Front Ventilated Disc Brake Rotor Min. Thickness	26.4 mm (1.039 in.)
Rear Ventilated Disc Brake Rotor Min. Thickness	20.0 mm (0.787 in.)
Front Disc Brake Calipers	Dual Piston Floating
Rear Disc Brake Calipers	Single Piston Floating
Rear Drum in Hat Diameter	206.1 mm (8.11 in.)
Rear Drum in Hat Cage Diameter	205.4 mm (8.08 in.) – 205.7 mm (8.09 in.)

**TORQUE SPECIFICATIONS**

DESCRIPTION	N·m	Ft. Lbs.	In. Lbs.	Comments
Brake Booster Nuts	30	22	—	
Brake Hose Frame Bolt	11	8	—	
Brake Rotor Splash Shield Bolts	10	7	—	
Electric Vacuum Pump (EVP) Bolts	8	—	71	
Electric Vacuum Pump (EVP) Bracket Bolts	25	18	—	
Front Brake Hose Axle Bolt	8	—	71	
Front Brake Hose Lower Control Arm Nut	18	13	—	
Front Caliper Bolts	37	27	—	
Front Caliper Brake Hose Banjo Bolt	35	26	—	
Front Brake Line Hose Flare Nut	20	15	—	
Front Caliper Adapter Bolt	195	144	—	
Front Rotor Screw	20	15	—	
Front Caliper Bleed Screw	10	7	—	
Master Cylinder Brake Line Flare Nuts	23	17	—	
Master Cylinder Nuts	18	13	—	
Park Brake Cable Boot Nuts	9	—	80	
Park Brake Cable Guide Nut	11	8	—	

DESCRIPTION	N·m	Ft. Lbs.	In. Lbs.	Comments
Park Brake Cable Bracket Bolts	70	52	—	
Park Brake Lever Sled Nuts	24	18	—	
Park Brake Lever Nuts	22	16	—	
Pedal Sled Nuts	30	22	—	
Rear Caliper Bleed Screw	10	7	—	
Rear Caliper Bolts	37	27	—	
Rear Rotor Screw	20	15	—	
Rear Caliper Adapter Bolt	125	92	—	
Rear Brake Line Hose Flare Nut	20	15	—	
Rear Caliper Brake Hose Banjo Bolt	35	26	—	
Rear Brake Line Intermediate Flare Nut	18	13	—	