Choose the right oil for your vehicle

Passenger vehicle engine oil selection table*

Advanced synthetic																										
	Mobil 1™ Extended Performance				Mobil 1™ High Mileage		Mobil 1™ Advanced Fuel Economy**			Mobil 1™				Mobil 1™ FS			Mobil 1™ ESP			Mobil 1™ ESP X2	Mobil 1™ ESP Formula	Mobil Delvac 1™ Advanced Fuel Economy	Mobil Delvac 1™ ESP	Mobil 1™ Truck & SUV		
Specs	**0W-20**	**5W-20**	**5W-30**	**10W-30**	**5W-20**	**5W-30**	**0W-16**	**0W-20**	**0W-30**	**5W-20**	**5W-30**	**10W-30**	**15W-50**	**0W-40**	**5W-40**	**X2 5W-50**	**0W-30**	**5W-30**	**X3 0W-40**	**0W-20**	**0W-40**	**5W-30**	**5W-40**	**0W-20**	**5W-20**	**5W-30**
AAE (STO 003) Group B7														√												
ACEA A3/B3													√	√	√	√										
ACEA A3/B4														√		√										
ACEA A5/B5			√	√		√																				√
ACEA A5/B5-16																										
ACEA C2																		√	√							
ACEA C3																	√	√	√							
ACEA C5																				√						
ACEA E7/E9																										
API CF	√	√	√	√	√	√		√	√	√	√	√	√	√	√	√		√	√							
API CI-4																							√			
API CI-4 PLUS																							√			
API CJ-4																							√			
API CK-4																							√			
AP FA-4																						√				
API SJ	√	√	√	√	√	√	√	√	√	√	√	√	√	√	√	√	√	√	√	√		√	√	√	√	√
API SL	√	√	√	√	√	√	√	√	√	√	√	√	√	√	√	√	√	√	√	√		√	√	√	√	√
API SM	√	√	√	√	√	√	√	√	√	√	√	√	√	√	√	√		√	√			√	√	√	√	√
API SN	√	√	√	√	√	√	√	√	√	√	√	√	√	√	√	√		√	√			√	√	√	√	√
API SN PLUS	√	√	√	√	√	√	√	√	√	√	√	√							√					√	√	√
API SP	√	√	√	√	√	√	√	√	√	√	√	√												√	√	√
Caterpillar ECF-3																								√	√	√
Chrysler MS 6395	√	√			√			√																√	√	
Cummins CES 20081																							√			
Cummins CES 20086																							√			
Cummins CES 20087																						√				
GM dexosD Licensed																				√						
GM dexos1: Gen2	√	√	√					√	√	√	√													√		√
GM dexos2																		√	√		√					
GM 6094M	√	√	√	√				√	√	√	√	√												√	√	√
FIAT 9.55535-M2														√												
FIAT 9.55535-S2																			√							
Ford WSS-M2C214-B1																						√				
Ford WSS-M2C929-A			√			√			√		√															√
Ford WSS-M2C930-A		√			√					√															√	
Ford WSS-M2C937-A														√												

Continue to next page >>>

Advanced synthetic

	Mobil 1™ Extended Performance				Mobil 1™ High Mileage		Mobil 1™ Advanced Fuel Economy**			Mobil 1™				Mobil 1™ FS			Mobil 1™ ESP			Mobil 1™ ESP X2	Mobil 1™ ESP Formula	Mobil Delvac 1™ Advanced Fuel Economy	Mobil Delvac 1™ ESP	Mobil 1™ Truck & SUV		
Specs	**0W-20**	**5W-20**	**5W-30**	**10W-30**	**5W-20**	**5W-30**	**0W-16**	**0W-20**	**0W-30**	**5W-20**	**5W-30**	**10W-30**	**15W-50**	**0W-40**	**5W-40**	**X2 5W-50**	**0W-30**	**5W-30**	**X3 0W-40**	**0W-20**	**0W-40**	**5W-30**	**5W-40**	**0W-20**	**5W-20**	**5W-30**
Ford WSS-M2C945-A		√			√					√															√	
Ford WSS-M2C945-B1		√			√					√															√	
Ford WSS-M2C946-A			√			√			√		√															√
Ford WSS-M2C946-B1			√			√					√															√
Ford WSS-M2C947-A	√							√																√		
Ford WSS-M2C947 B1	√							√																√		
Ford WSS-M2C953-A									√																	
Ford WSS-M2C953-B1									√																	
Ford WSS-M2C960-A1		√			√					√															√	
Ford WSS-M2C961-A1			√			√					√															√
Ford WSS-M2C962-A1	√							√																√		
Ford WSS-M2C963-A1									√																	
ILSAC GF-6A	√	√	√	√	√	√		√	√	√	√	√												√	√	√
ILSAC GF-6B							√																			
Honda HTO-06			√								√															
MB 228.61																						√				
MB 229.1																√										
MB 229.31																	√	√	√							
MB 229.3														√	√	√										
MB 229.5														√	√											
MB 229.51																	√	√	√							
MB 229.52																	√	√	√							
MB 229.71																				√						
Nissan Genuine Performance														√												
Porsche A40														√	√	√										
Porsche C20																				√						
Porsche C30																	√	√								
Porsche C40																			√							
PSA B 71 2290																		√								
PSA B 71 2297																		√								
STJLR.51.5122																				√						
STJLR.03.5006																				√						
VW 501.01																										
VW 502.00														√	√			√								
VW 503.00																		√								
VW 503.01														√				√								
VW 504.00																	√	√								
VW 505.00														√	√			√								
VW 505.01																										
VW 506.00																		√								
VW 507.00																	√	√								
VW 508.00																				√						
VW 509.00																				√						
VW 511.00																			√							

Synthetic

	Mobil Super™ Synthetic				
Specs	**0W-16**	**0W-20**	**5W-20**	**5W-30**	**Euro 5W-40**
API SJ	√	√	√	√	√
API SL	√	√	√	√	√
API SM	√	√	√	√	√
API SN	√	√	√	√	√
API SN Plus	√	√	√	√	√
API SP	√	√	√	√	
BMW Longlife 01					√
Chrysler MS-6395*		√		√	
Ford WSS-M2C929-A				√	
Ford WSS-M2C930-A			√		
Ford WSS-M2C945-A			√		
Ford WSS-M2C945-B1			√		
Ford WSS-M2C946-A				√	
Ford WSS-M2C946-B1				√	
Ford WSS-M2C947-A		√			
Ford WSS-M2C947-B1		√			
Ford WSS-M2C960-A1			√		
Ford WSS-M2C961-A1				√	
Ford WSS-M2C962-A1		√			
GM 6094M			√		
GM dexos1: Gen2		√		√	
ILSAC GF-6A		√	√	√	
ILSAC GF 6-B	√				
MB-Approval 229.3					√
MB-Approval 229.5					√
Porsche A40					√
VW 502 00					√
VW 505 00					√

High Mileage, Synthetic blend

	Mobil Super™ High Mileage		
Specs	**5W-20**	**5W-30**	**10W-30**
API SJ, SL, SM, SN, SN Plus, SP	√	√	√
Chrysler MS-6395	√	√	√
Ford WSS-M2C929-A		√	
Ford WSS-M2C930-A	√		
Ford WSS-M2C945-A	√		
Ford WSS-M2C945-B1	√		
Ford WSS-M2C946-A		√	
Ford WSS-M2C946-B1		√	
Ford WSS-M2C960-A1	√		
Ford WSS-M2C961-A1		√	
GM 6094M	√	√	√
ILSAC GF-6A	√	√	√

Synthetic blend

	Mobil Special™		
Specs	**5W-20**	**5W-30**	**10W-30**
API SJ, SL, SM, SN, SN Plus, SP	√	√	√
Chrysler MS-6395	√	√	√
Ford WSS-M2C929-A		√	
Ford WSS-M2C930-A	√		
Ford WSS-M2C945-A	√		
Ford WSS-M2C945-B1	√		
Ford WSS-M2C946-A		√	
Ford WSS-M2C946-B1		√	
Ford WSS-M2C960-A1	√		
Ford WSS-M2C961-A1		√	
GM 6094M	√	√	√
ILSAC GF-6A	√	√	√

Automatic transmission fluid selection table* Automatic transmission fluids

Brand name	Product description	Recommended consumer applications
Mobil 1™ Synthetic ATF	Advanced Full Synthetic multi-vehicle automatic transmission fluid that outperforms conventional automatic transmission fluids and offers exceptional thermal stability.	GM Dexron, Ford Mercon, Ford Mercon V, JASO 1-A, MAN 339 V1, Volvo 97340
Mobil™ Multi-Vehicle ATF	Premium Full Synthetic multi-vehicle automatic transmission fluid formulated for use in a wide variety of vehicles from North American, Europe and Asia.	Ford Mercon V, Mercon LV, GM Dexron VI, GM Dexron III, GM Dexron II, GM Dexron IID, GM Dexron IIE, GM Dexron IIIG, GM Dexron IIIH, JASO 1-A, Allison C-4. For a detailed list of suitable applications, please refer to the product data sheet or mobil.ca.
Mobil™ Dexron VI ATF	High-performance, synthetic blend formulation that meets or exceeds the stringent requirements of GM's Dexron-VI specification and provides warranty protection for 2006 and newer GM vehicles. It also provides improved performance in older GM vehicles wherever Dexron is specified.	GM Dexron-VI
Mobil™ ATF D/M	Synthetic Blend lubricant that provides excellent oxidation and friction stability, anti-wear properties, and low-temperature fluidity desired for many automatic transmissions.	GM Dexron II, GM Dexron IIIH, Ford Mercon and Allison C-4
Mobil™ ATF +4	Specifically formulated to ensure optimal performance in Chrysler automatic transmissions. Its unique additive package provides the proper frictional properties, excellent low-temperature fluidity and dependable wear protection.	Services that specify an ATF+, ATF+2, ATF+3 and AFT+4, Chrysler MS9602 and Mitsubishi and Hyundai applications where an MS-9602 type fluid is specified.
Mobil™ ATF 3309	High-performance lubricant that meets original equipment manufacturers' specifications for use in certain slip-controlled lock-up automatic transmissions.	Transmissions requiring fluids of JWS 3309 or GM 9986195 quality levels. It is also recommended for service fill applications where Toyota T-IV or T4, T-III or T3 are called for Audi G-055-025-A2, Ford WSS-M2C924-A.

Due to continual product development, the information in this chart is subject to change without notification. This chart is current as of September 1, 2021. This chart is provided solely for general informational purposes, and Imperial Oil accepts no responsibility for any decisions made or actions taken based on the information contained in this guide. Before making any decision or taking any action please refer to our Product Data Sheets found at **mobil.ca/pds** for the most current product information.

For additional information please call our Technical Support Center at **1-888-968-3776** or visit **mobil.ca.**

*For a full list of Industry and original equipment manufacturer approvals by product and viscosity, see the Product Data Sheets available online at mobil.ca
**Potential fuel economy improvement obtained by switching from higher viscosity oils to a lower viscosity grade.
Actual savings are dependent upon vehicle/engine type, outside temperature, driving conditions and your current engine oil viscosity.

© 2021 ExxonMobil. Mobil, Mobil 1 and Mobil Super are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries. Imperial Oil, licensee. Other trademarks shown are property of their respective owners.