



Jeep
Gladiator, JT
Gladiator 3.0 Diesel (2019 -)

Drive Type	AWD
Fuel	Diesel
Engine build	V
Cylinders	6
Valves per cylinder	4
Displacement	2987 cc
Power rating	264 hp / 194 kW

Engine EXJ

Capacity:	Capacity 9 US quarts Service fill
Use:	Flexible (max)
Interval:	Change 10000 miles/ 12 months
Recommendation:	Click here to contact the Phillips 66 Technical Hotline for product recommendations or call 877.445.9198.

Use:	Severe
Interval:	Change 4000 miles
Recommendation:	Click here to contact the Phillips 66 Technical Hotline for product recommendations or call 877.445.9198.

Differential, rear, with trailer towing package

Capacity:	Capacity 1.6 US quarts
Use:	Normal
Interval:	Check 20000 miles/ 24 months
Recommendation:	Click here to contact the Phillips 66 Technical Hotline for product recommendations or call 877.445.9198.

Use:	Severe
Interval:	Change 20000 miles/ 24 months
Recommendation:	Click here to contact the Phillips 66 Technical Hotline for product recommendations or call 877.445.9198.

Differential, rear, limited slip, with trailer towing package

Capacities:	Capacity 1.6 US quarts Capacity 0.074 US quarts LS-additive
Use:	Severe
Interval:	Change 20000 miles/ 24 months
Recommendation:	Click here to contact the Phillips 66 Technical Hotline for product recommendations or call 877.445.9198.

Use:	Initial service
Interval:	Check 20000 miles/ 24 months
Recommendation:	Click here to contact the Phillips 66 Technical Hotline for product recommendations or call 877.445.9198.

Transmission, automatic ZF 8HP75 8/1

Capacity:	Capacity 9.5 US quarts
Use:	Normal
Recommendation:	(year-round) Versatrans® CVT PLUS ATF

Transferbox MP 1622

Capacity:	Capacity 1.7 US quarts
Use:	Normal
Interval:	Check 30000 miles/ 36 months
Recommendation:	(year-round) Versatrans® CVT PLUS ATF (year-round) Versatrans® LV ATF (year-round) Versatrans® ATF

Use:	Severe
Interval:	Change 120000 miles/ 72 months
Recommendation:	(year-round) Versatrans® CVT PLUS ATF (year-round) Versatrans® LV ATF (year-round) Versatrans® ATF

Transferbox MP 3022C

Capacity:	Capacity 1.9 US quarts
Use:	Normal
Interval:	Check 30000 miles/ 36 months
Recommendation:	(year-round) Versatrans® CVT PLUS ATF (year-round) Versatrans® LV ATF (year-round) Versatrans® ATF

Use: Severe
Interval: Change 120000 miles/ 72 months
Recommendation: (year-round) Versatrans® CVT PLUS ATF
(year-round) Versatrans® LV ATF
(year-round) Versatrans® ATF

Differential, front 210 FBI

Capacity: Capacity 1.1 US quarts
Use: Normal
Interval: Check 20000 miles/ 24 months
Recommendation: (temperate climate) SHP® Syngear FE SAE 75W-90

Use: Severe
Interval: Change 20000 miles/ 24 months
Recommendation: (year-round) SHP® Syngear FE SAE 75W-90

Differential, rear, limited slip 220 RBI

Capacities: Capacity 1.6 US quarts
Capacity 0.074 US quarts LS-additive
Use: Normal
Interval: Check 20000 miles/ 24 months
Recommendation: Click here to contact the Phillips 66 Technical Hotline for product recommendations or call 877.445.9198.

Use: Severe
Interval: Change 20000 miles/ 24 months
Recommendation: Click here to contact the Phillips 66 Technical Hotline for product recommendations or call 877.445.9198.

Differential, rear 220 RBI

Capacity: Capacity 1.2-1.5 US quarts
Use: Normal
Interval: Check 20000 miles/ 24 months
Recommendation: (temperate climate) SHP® Syngear FE SAE 75W-90

Use: Severe
Interval: Change 20000 miles/ 24 months
Recommendation: (year-round) SHP® Syngear FE SAE 75W-90

© Olyslager 2024 All rights reserved. <https://www.phillips66.com/privacy-statement>. No part of this information may be reproduced, stored in any retrieval system, or transmitted in any form or by any means without any prior written permission from Olyslager Organisation B.V.. Although every care is taken to ensure accuracy and completeness in compiling these data, no liability, other than that which may not be excluded by law, can be accepted for damage or loss caused by any errors or omissions in the information given. By accessing and using this oil recommendation information, the user confirms that he/she has the experience, the knowledge and the ability to perform the required maintenance activity in a safe and responsible manner. He/she also holds harmless and indemnifies the publisher against any loss, injury, claim and penalties arising from the wrongful interpretation or incorrect usage of the published information. Data release: 2024-01

