



Jeep
Gladiator, JT
Gladiator 3.6 (2019 -)

Drive Type	AWD
Fuel	Gasoline
Engine build	V
Cylinders	6
Valves per cylinder	4
Displacement	3604 cc
Power rating	288 hp / 212 kW

Engine Pentastar

Capacity:	Capacity 5 US quarts Service fill
Use:	Flexible (max)
Interval:	Change 10000 miles/ 12 months
Recommendation:	(year-round) GT-1® Max SAE 0W-20 (year-round) GT-1® HP Elite SAE 0W-20 (year-round) GT-1® High Performance SAE 0W-20

Use:	Severe
Interval:	Change 4000 miles
Recommendation:	(year-round) GT-1® Max SAE 0W-20 (year-round) GT-1® HP Elite SAE 0W-20 (year-round) GT-1® High Performance SAE 0W-20

Differential, rear, with trailer towing package

Capacity:	Capacity 1.6 US quarts
Use:	Normal
Interval:	Check 40000 miles/ 48 months
Recommendation:	Click here to contact the Phillips 66 Technical Hotline for product recommendations or call 877.445.9198.

Use:	Severe
Interval:	Change 40000 miles/ 48 months
Recommendation:	Click here to contact the Phillips 66 Technical Hotline for product recommendations or call 877.445.9198.

Use:	Initial service
Interval:	Check 20000 miles/ 24 months
Recommendation:	Click here to contact the Phillips 66 Technical Hotline for product recommendations or call 877.445.9198.

Differential, rear, limited slip, with trailer towing package

Capacities:	Capacity 1.6 US quarts Capacity 0.074 US quarts LS-additive
Use:	Normal
Interval:	Check 40000 miles/ 48 months
Recommendation:	Click here to contact the Phillips 66 Technical Hotline for product recommendations or call 877.445.9198.

Use:	Severe
Interval:	Change 40000 miles/ 48 months
Recommendation:	Click here to contact the Phillips 66 Technical Hotline for product recommendations or call 877.445.9198.

Use:	Initial service
Interval:	Check 20000 miles/ 24 months
Recommendation:	Click here to contact the Phillips 66 Technical Hotline for product recommendations or call 877.445.9198.

Transmission, manual AL6 6/1

Capacity:	Capacity 2.4 US quarts Dry fill
Use:	Normal
Recommendation:	(year-round) Versatrans® CVT PLUS ATF (year-round) Versatrans® LV ATF (year-round) Versatrans® ATF

Use:	Severe
Interval:	Change 30000 miles/ 36 months
Recommendation:	(year-round) Versatrans® CVT PLUS ATF (year-round) Versatrans® LV ATF (year-round) Versatrans® ATF

Transferbox MP 1622

Capacity:	Capacity 1.7 US quarts
Use:	Normal
Interval:	Check 30000 miles/ 36 months
Recommendation:	(year-round) Versatrans® CVT PLUS ATF (year-round) Versatrans® LV ATF (year-round) Versatrans® ATF

Use: Severe
Interval: Change 60000 miles/ 72 months
Recommendation: (year-round) Versatrans® CVT PLUS ATF
(year-round) Versatrans® LV ATF
(year-round) Versatrans® ATF

Transferbox MP 3022C

Capacity: Capacity 1.9 US quarts
Use: Normal
Interval: Check 30000 miles/ 36 months
Recommendation: (year-round) Versatrans® CVT PLUS ATF
(year-round) Versatrans® LV ATF
(year-round) Versatrans® ATF

Use: Severe
Interval: Change 60000 miles/ 72 months
Recommendation: (year-round) Versatrans® CVT PLUS ATF
(year-round) Versatrans® LV ATF
(year-round) Versatrans® ATF

Transmission, automatic 8HP50 850RE 8/1

Capacity: Capacity 9.5 US quarts
Use: Normal
Recommendation: (year-round) Versatrans® CVT PLUS ATF

Differential, front 210 FBI

Capacity: Capacity 1.1 US quarts
Use: Normal
Interval: Check 40000 miles/ 48 months
Recommendation: (temperate climate) SHP® Syn gear FE SAE 75W-90

Use: Severe
Interval: Change 40000 miles/ 48 months
Recommendation: (year-round) SHP® Syn gear FE SAE 75W-90

Use: Initial service
Interval: Check 20000 miles/ 24 months
Recommendation: (temperate climate) SHP® Syn gear FE SAE 75W-90

Differential, rear, limited slip 220 RBI

Capacities:	Capacity 1.6 US quarts Capacity 0.074 US quarts LS-additive
Use:	Normal
Interval:	Check 40000 miles/ 48 months
Recommendation:	Click here to contact the Phillips 66 Technical Hotline for product recommendations or call 877.445.9198.

Use:	Severe
Interval:	Change 40000 miles/ 48 months
Recommendation:	Click here to contact the Phillips 66 Technical Hotline for product recommendations or call 877.445.9198.

Use:	Initial service
Interval:	Check 20000 miles/ 24 months
Recommendation:	Click here to contact the Phillips 66 Technical Hotline for product recommendations or call 877.445.9198.

Differential, rear 220 RBI

Capacity:	Capacity 1.2-1.5 US quarts
Use:	Normal
Interval:	Check 40000 miles/ 48 months
Recommendation:	(year-round) SHP® Syngear FE SAE 75W-90

Use:	Severe
Interval:	Change 40000 miles/ 48 months
Recommendation:	(year-round) SHP® Syngear FE SAE 75W-90

Use:	Initial service
Interval:	Check 20000 miles/ 24 months
Recommendation:	(temperate climate) SHP® Syngear FE SAE 75W-90

© [Olyslager](#) 2024 All rights reserved. <https://www.phillips66.com/privacy-statement>. No part of this information may be reproduced, stored in any retrieval system, or transmitted in any form or by any means without any prior written permission from Olyslager Organisation B.V.. Although every care is taken to ensure accuracy and completeness in compiling these data, no liability, other than that which may not be excluded by law, can be accepted for damage or loss caused by any errors or omissions in the information given. By accessing and using this oil recommendation information, the user confirms that he/she has the experience, the knowledge and the ability to perform the required maintenance activity in a safe and responsible manner. He/she also holds harmless and indemnifies the publisher against any loss, injury, claim and penalties arising from the wrongful interpretation or incorrect usage of the published information. Data release: 2024-01